

Model Specifications

		BOWRIDERS							CUDDIES / CRUISERS							SPORT
		185 LS/LX	195 LS/LX/LR	195 FX	205 LS/LX/LR	220 DR	225 LR	230 LX	250 LR	195 CS/CX	205 CS/CX	225 CR	240 CS	250 CR	250 CS	230 SX
1	Length Overall	ft 18' 5" 5.6	19' 6" 5.9	19' 6" 5.9	20' 11" 6.4	22' 3" 6.7	22' 11" 7.0	22' 8" 6.9	25' 0" 7.6	19' 6" 5.9	20' 11" 6.4	22' 11" 7.0	23' 6" 7.1	25' 0" 7.6	25' 0" 7.6	22' 8" 6.9
8	Beam	in 85 216	91 231	91 231	93 236	99 251	100 254	96 244	102 259	91 231	93 236	100 254	102 259	102 259	102 259	96 244
	Bridge Clearance	in 41 104	47 119	49 124	47 119	61 155	52 132	53 135	65 165	52 132	50 127	55 140	76 193	65 165	77 196	52 132
	Dry Weight ¹ (w/ popular engine)	lb 2219 3.0L	2604 4.3L	2672 4.3L	2891 5.0L MPI	3987 5.0L	3364 5.0L MPI	3269 5.0L MPI	4340 5.0L MPI	2734 4.3L	2990 5.0L MPI	3539 5.0L MPI	4429 5.0L MPI	4293 5.0L MPI	4971 5.0L MPI	3464 5.0L MPI
	Fuel Capacity	gal 21 80	21/35* 79/133	21/35* 79/133	35 133	62 235	57 216	57 216	68 257	21/35* 79/133	35 133	57 216	68 257	68 257	68 257	57 216
	Water Capacity	gal liter				17 64			17 64		3 11	6 23	19 72	17 64	25 95	3 11
	Ice Box Capacity	qt liter	32 30	32 30	32 30	28+25+32 26+24+30	32+25 30+24	46+32 44+30	32+32+25 30+30+24	46 44	46 44	32+25 30+24	48+25 45+24	32+25 30+24	32+25 30+24	46 44
	Max Capacity	ppl/lb ppl/kg	7/1070 7/485	8/1470 8/667	8/1470 8/667	8/1700 8/771	11/2365 11/1073	10/2080 10/943	8/1850 8/839	10/2265 10/1027	8/1470 8/667	8/1700 8/771	10/2080 10/943	10/2265 10/1027	10/2265 10/1027	8/1850 8/839
	Free Board	in cm	23 58	24 61	24 61	24 61	36 91	26 66	37 94	23 58	24 61	26 66	45 114	37 94	45 114	24 61
	Molded Depth (Windshield Base to Keel)	in cm	42 107	44 112	44 112	46 117	62 157	51 130	66 168	47 119	49 123	54 137	77 196	66 168	78 198	50 127
	Max Depth (Including Windshield)	in cm	52 132	55 140	55 140	57 145	72 183	58 147	77 196	60 152	62 157	61 155	91 231	77 196	92 234	60 152
	Max Draft (Drive Down)	in cm	29 74	31 79	31 79	31 79	34 86	33 84	36 91	31 79	31 79	33 84	34 86	34 86	35 89	36 91
	Max Draft (Drive Up - +5" on V 3.0; +4" on B1 & B3)	in cm	18 46	18 46	18 46	17 43	17 43	18 46	19 48	17 43	17 43	18 46	17 43	17 43	19 48	20 51
2	Bow Depth (Bow to Cushion Top)	in cm	14 36	15 38	15 38	16 41	16 41	20 51	17 43	25 64	28 71	28 71	38 97	32 81	40 102	24 61
3	Bow Depth (Max Depth)	in cm	31 79	32 81	32 81	32 81	33 84	34 86	33 84	41 104	45 114	49 124	71 180	58 147	72 183	45 114
4	Bow Length (Max Length)	in cm	56 142	58 147	58 147	58 147	64 163	59 150	68 173	60 152	76 193	81 206	111 282	68 173	118 300	95 241
5	Cockpit Depth (At Helm)	in cm	28 71	29 74	29 74	29 74	33 84	33 84	32 81	34 86	34 86	36 91	36 91	36 91	35 89	32 81
6	Cockpit Width (Max Molded)	in cm	69 175	73 185	73 185	74 188	81 206	81 206	78 198	73 185	74 188	81 206	78 198	79 201	78 198	78 198
7	Cockpit Length (Max Molded)	in cm	102 259	107 272	107 272	110 279	114 290	103 262	93 236	114 290	110 279	94 239	114 290	119 302	117 297	93 236
	Sleeping Capacity					2			2	2+1	2+1	2+1	4	2+2	2+2+1	2
	Transom Angle		15°	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°
	Deadrise Angle		19°	19°	19°	19°	16°	20°	20°	19°	19°	20°	21°	21°	21°	20°

* Fuel capacity is 21 gal. with 3.0L, 35 gal. with 4.3L.
1 Weights vary depending on installed options. Refer to Performance Options for additional information.

Specifications are subject to change without notice or obligation. For current information, visit StingrayBoats.com/specifications

